

Temp-Tec NL-517

DESCRIPTION AND GENERAL PROPERTIES

- **Material** Neoprene
- **Length (inches)** 17
- **Thickness (inches)** Heavy Weight
- **Colour/Color** Black / Blue
- **Interior finish** Knitted thermal protection
- **Exterior finish** Pebbled
- **Size / EAN** 8 9 10
- **Packaging** 1 pair/bag - 6 pairs/carton



PERFORMANCE RESULTS

Certification category 3

CE 0334



111



02XXXX



ACJKL



2212

Legends



MECHANICAL HAZARDS EN 388

PERFORMANCE LEVELS

0-4 0-5 0-4 0-4
 └─ Puncture resistance
 └─ Tear resistance
 └─ Blade cut resistance
 └─ Abrasion resistance



LOW CHEMICAL PROTECTION EN 374



MICRO-ORGANISMS EN 374



RADIOACTIVE CONTAMINATION EN 421



HEAT AND FIRE EN 407

PERFORMANCE LEVELS

0-4 0-4 0-4 0-4 0-4 0-4
 └─ Resistance to large quantities of molten metal
 └─ Resistance to small drops of molten metal
 └─ Radiant heat resistant
 └─ Convective heat resistance
 └─ Contact heat resistance
 └─ Burning behaviour



SPECIFIC CHEMICAL PROTECTION EN 374

Letter Code	Chemical product
A	Methanol
B	Acetone
C	Acetonitrile
D	Dichloromethane
E	Carbon Disulfide
F	Toluene
G	Diethylamine
H	Tetrahydrofurane
I	Ethyl acetate
J	n-Heptane
K	Sodium hydroxide 40%
L	Sulphuric acid 96%



COLD HAZARDS EN 511

PERFORMANCE LEVELS

0-4 0-4 0 or 1
 └─ Water permeability
 └─ Contact cold resistance
 └─ Convective cold resistance

For more details: www.mapa-pro.com

MAPA[®]
PROFESSIONAL

SPECIFIC ADVANTAGES

- Multi-purpose chemical resistance (acids, aliphatic solvents) increased by the thickness of the material
- Excellent thermal insulation, due to double-knit cotton
- Good grip of wet or slippery objects,

MAIN FIELDS OF USE

Other industries

- Boiler room work
- Handling of hot piping
- Handling of moulds in the ceramic industry
- Manufacture of adhesives
- Manufacture of insulating electric wires
- Road works in cold conditions
- Steam cleaning

Food industry

- Filleting Fish

Rubber industry

- Polymer extrusion

Mechanical industry

- Chemical treatment of metals
- Oil quenching of steel

Petrochemical industry

- Sampling of hot petrochemical products

INSTRUCTIONS FOR USE

Instructions for use

- It is recommended to check that the gloves are suitable for the intended use, because the conditions of use at workplace may differ from the "CE"-type tests. For very high or low temperatures, be careful that a sustained contact does not cause burns.
- It is not recommended for persons sensitized to dithiocarbamates to use these gloves.
- Put the gloves on dry, clean hands.
- Do not use the gloves in contact with a chemical for a duration in excess of the measured breakthrough time. Refer to the website www.mapa-pro.com or contact the Technical Customer Service - MAPA PROFESSIONAL (stc.mapaspontex@mapaspontex.fr) in order to know this breakthrough time. Use 2 pairs alternatively when in long duration contact with a solvent.
- Turn the cuff end down in order to prevent a hazardous chemical from dripping onto the arm.
- Ensure the inside of the gloves is dry before putting them on again.

Storage conditions

- Store the gloves in their original packaging at a temperature not below 5°C.

Laundering conditions

- Before taking off the gloves, clean them as appropriate :
- in use with paints, pigments and inks : wipe with a clean cloth dampened with a suitable solvent, and rub over with a dry cloth
- in use with a solvent (diluent, etc...) : rub over with a dry cloth
- in use with acids or alkalies : thoroughly rinse the gloves under running water, and rub over with a dry cloth
- Caution : improper use of the gloves or submitting them to a cleaning or laundering process that is not specifically recommended can alter their performance levels.

Food contact US

- FDA 21CFR 177.2600

LEGISLATION

- This product is not classified as hazardous according to the directive 1999/45/EC of the European Parliament and of the Council.

- This product does not contain any substances of very high concern according to the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).

- **UE type certificate or CE type examination certificate** : 0072/014/162/06/98/0129
- **Issued by the notified body nr** : 0072 - I.F.T.H. – av. Guy de Collongue - F-69134 ECULLY CEDEX
- **Quality assurance certificat** : 0334 Asqual 14 rue des Reculettes -F-75013 PARIS